Edgewood Ave 6000 S

OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION ____11_TOWNSHIP_ 14 RANGE __3_ DATE: 5-25-05 05 PARTY CHIEF: Whiteside CREW: -Po. TYPE OF MARKER: Harrison (capless) METHOD OF ESTABLISHMENT: ____County: 10-02-00 IN. S.P.C. E ZONE NAD '83 14031102 491972.8147(m) NAME: N: E: 56987.1906(m) Edgewood Ave 6000 S 202.54 2. 142.03 (PWP)

Original post set 1820 by Laughlin with witness: 14" sugar S 12 __ 12 links, 20" beech N 34 E 34 links per Marion County Atlas pg. 5. Rock set 1850 by Hosbrook with witness: 28" ook S 25 W 65 links, 5-8-53 Monroe called a boot spike over stone. 5-23-58 Monroe called same. 5-8-70 McLand called PK nail. 6-11-75 Miller called same. 10-7-86 Greene called same. 6-4-90 excavated and PK nail found at surface. Square steel bolt found 5" down. No stone found. Harrison set. Re-tied 5-16-96. Re-tied 5-25-05 by Whiteside.

Ranke

3.

14031102		
REF.	DISTANCE	DESCRIPTION
Ĭ.	47.74	PK nail W PwP#44-725 8"up
2.	202.54	Top nut of fire hydrant
3.	65.47	PK mail F PwP#558-725 8"up
4.	13.98'	PK nail F PwP3379-725 6"up
5.	142.03'	PK nail N PwP#25-724 12"up
6-	45.13'	Mag nail w/washer SW PwP#146-724 3"up
7.	122.66'	SF corner of brick ADDRESS 510